

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 February 2003 (27.02.2003)


PCT

(10) International Publication Number
WO 03/016777 A1

- (51) International Patent Classification⁷: F17C 13/08, 1/02
- (21) International Application Number: PCT/IT02/00526
- (22) International Filing Date: 7 August 2002 (07.08.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
MC2001A000086 20 August 2001 (20.08.2001) IT
- (71) Applicant (for all designated States except US): SIDA ENGINEERING-S.R.L. [IT/IT]; 60, Via Esino, I-60020 Ancona (IT).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): LUONGO, Nicantonio [IT/IT]; 10, Via Basilicata, I-60015 Falconara Marittima (IT).
- (74) Agent: BALDI, Claudio; 4, Piazza Ghislieri, I-60035 Jesi (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: MULTI-CELL TANK FOR PRESSURISED GAS



(57) Abstract: The present invention relates to a multi-cell tank (2) for pressurised gas formed by a group of tubes (2a) immersed in a fibrous resin body (4) and reinforced by means of external texture (7), closed with two covers that feature a intercommunicating series of domes on the internal side, which exactly match the opening of the tubes of the group.

WO 03/016777 A1

BEST AVAILABLE COPY



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent

- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Description

Multi-cell tank for pressurised gas

The present patent application for industrial invention relates to a multi-cell tank for pressurised gas with modular structure that allows it to be realised with variable volume and capacity according to the use and installation place of the tank.

5 Although the main use for this tank is in natural gas vehicles, it is understood that the tank can be used to store any type of high-pressure technical gas.

10 The tank of the invention is an alternative solution to traditional steel cylinders, with several advantages, such as higher operating safety, easier internal inspection during re-testing, lower weight, higher flexibility in terms of shapes and volumes at the same capacity.

15 The characteristics of the tank of the invention result from its basic constructive configuration, according to which the total capacity of the tank is given by multiple cylindrical cells in parallel intercommunicating position, realised with a group of thin tubes, to which mechanical resistance is given through an external reinforcement coating of composite resins.

20 More precisely, the tank of the invention comprises a group of tubes supported by spacing plates with a parallel close series of holes suitable for housing similar tubes that are placed in such a way that each tube is almost in contact with the adjacent tubes in order to reduce dimensions.

The group of tubes is immersed in fibrous resin that fills all the spaces in the group of tubes, flush with the borders of the spacing plates.

25 The two ends of the group of tubes are sealed with two closing covers that feature an intercommunicating series of hemispherical domes on the internal side, which exactly match the opening of the tubes in the group.

The two covers are joined to the group of tubes by means of tie rods passing through the spaces in the group of tubes.

The group of tubes immersed in fibrous resin is reinforced by wrapping

it in a resin-bonded texture with continuous wire, on which a second texture with resin-bonded longitudinal wires is laid in order to join the two covers.

Finally, the tank of the invention is housed in a suitable pre-formed protection enclosure, preferably with aluminium sheet.

5 Based on this general description of the structural configuration of the tank, the advantages of the tank of the invention become evident with respect to traditional steel cylinders.

First of all, the tank of the invention can be given different shapes by selecting the appropriate number of tubes for each perimeter side.

10 The length of the tank can be changed by simply varying the length of the tubes in the group.

Moreover, the tank of the invention is characterised by a high capacity/weight ratio, thanks to the low specific weight of the materials used, that is thin metal tubes and fibrous resins, characterised by low specific weight and high mechanical resistance to tensile stress.

15 As regards the low thickness of the metal tubes, it must be noted that the tubes are not required to have good mechanical resistance, in view of the external fibrous resin coating which is reinforced with transversal and longitudinal texture.

20 In other words, the tubes only have a modelling function for the series of cylindrical cavities to be obtained in the fibrous resin body of the tank.

The higher operating safety of the tank of the invention derives from the fact that the resistant surface containing pressurised gas has been increased with respect to cylinders with the same capacity, thus reducing the mechanical stress suffered by the surfaces.

25 As regards the easier internal inspection of the tank, it must be noted that the group of tubes can be internally inspected and cleaned at any time, after removing the two covers. Once inspection and maintenance operations are completed, the two covers are positioned and the tank can be tested.

30 Currently, for internal inspection purposes, the internal cavity of cylinders is visually inspected through the hole where the gas delivery valve is inserted, after disassembling it. This means that the inspection is carried out

through a small hole with $\frac{3}{4}$ inch diameter, which is not sufficient to ensure total reliability of the control operation aimed to check the integrity of the internal walls of the cylinder.

For major clarity the description of the tank according to the present invention continues with reference to the enclosed drawings, which are intended for purposes of illustration and not in a limiting sense, whereby:

- fig. 1 is a view of the tank with right parallelepiped shape and rectangular base;
- fig. 2 is a view of the support spacing plate of the group of tubes;
- 10 - fig. 3 is a view of the group of tubes supported by spacing plates;
- fig. 4 is a view of the group of tubes immersed in fibrous resin;
- fig. 5 is a view of the group of tubes immersed in fibrous resin and reinforced with external texture;
- fig. 6 is a view of the tank provided with covers, not yet inserted in the protection enclosure, as shown in fig. 1;
- 15 - figs. 7 and 8 are cross-sections of fig. 6 with planes VII-VII and VIII-VIII;
- fig. 9 is a view of the tank with a different shape.

With reference to the enclosed figures, the tank (1) of the invention comprises a group of thin tubes (2) supported by spacing plates (3) with a parallel close series of holes (3a) suitable for housing similar tubes (2a) that are placed in such a way that each tube (2a) is almost in contact with the adjacent tubes in order to reduce dimensions, as shown in Fig. 3.

The group of tubes (2) is immersed in fibrous resin (4) that fills all the spaces in the group of tubes, including perimeter spaces, where the resin is perfectly flush with the borders of the spacing plates (3), as shown in Fig. 4.

The two ends of the group of tubes (2) are sealed with two closing covers (5) that feature a series of hemispherical domes (5a) on the internal side, which communicate through ducts (5b) and exactly match the opening of the tubes (2a) in the group, as shown in the enlarged view of Fig. 7A.

The two covers (5) are joined to the group of tubes (2) by means of tie rods (6) passing through the spaces in the group of tubes and through holes (3b) suitably provided on the spacing plates (3).

The group of tubes immersed in fibrous resin (4) is reinforced by wrapping it in a resin-bonded texture with continuous wire (7), as shown in Fig. 5.

5 A second texture (7a) with longitudinal direction only is laid over the first texture (7) in order to join the bottom covers applied and tightened with tie rods (6) to the group of tubes (2), as shown in Fig. 6.

The tank of the invention is housed in a suitable pre-formed protection enclosure (8), preferably with aluminium sheet, as shown in Fig. 1.

10 One of the bottom covers (5) is provided with a hole for the gas valve, of conventional type and for this reason not shown on the enclosed drawings.

It must be said that the gas valve can be placed in the most convenient position in the cover (5), since all hemispherical domes (5) intercommunicate through ducts (5b) and therefore the gas contained in the tubes (2a) can reach the valve through the net of intercommunicating domes (5a).




15 Fig. 9 has been enclosed with the only purpose to show the possibility of realising the tank of the invention with any shape, including an irregular shape, according to the space where the tank is installed.

20 This characteristic of the tank of the invention is extremely helpful and useful in case of natural gas tanks installed in vehicle trunks. The cylinders that are currently used for this application have low capacity since they cannot use the available space at best, being impossible to realise cylinders with suitable shape and dimensions according to the space in the trunk where the tank is usually installed.



Claims



- 1) A multi-cell tank for pressurised gas, characterised by the fact it comprises:
- a group of tubes (2) supported by spacing plates (3) with a parallel close series of holes (3a) suitable for housing similar tubes (2a) that are placed in such a way that each tube (2a) is almost in contact with the adjacent tubes;
 - a body of fibrous resin (4) that fills all the spaces in the group of tubes, including perimeter spaces, where the resin is perfectly flush with the borders of the spacing plates (3);
 - two bottom covers (5) that close the two ends of the group of tubes (2) and feature a series of hemispherical domes (5a) on the internal side, which communicate through ducts (5b) and exactly match the opening of the tubes (2a) in the group (2);
 - tie rods (6) that join the two covers (5) to the group of tubes (2) and pass through the spaces in the group of tubes and through holes (3b) suitably provided on the spacing plates (3);
 - an external reinforced layer realised by wrapping it in a resin texture with continuous wire (7), on which a second texture (7a) with longitudinal direction only is laid in order to join the bottom covers (5) applied and tightened with tie rods (6) to the group of tubes (2);
 - a pre-formed external protection enclosure (8), preferably with aluminium sheet;
 - an ordinary gas valve applied on a hole located on one of the two bottom covers (5).

1/4



2/4





4/4




FIG. 7a




FIG. 8




FIG. 7

INTERNATIONAL SEARCH REPORT

International Application No.

IT 02/00526

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 F17C13/08 F17C1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 F17C B60K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 757 248 A (EUROP PROPULSION) 19 June 1998 (1998-06-19) page 1, line 3-6; claims; figures page 1, line 22-30 page 2, line 26-34 page 3, line 25,26 page 5, line 28-34	1
P,A	US 2002/046773 A1 (PEMBERTON DAVID J ET AL) 25 April 2002 (2002-04-25) page 10, paragraph 128; figures 6-16 page 11, paragraph 134 page 12, paragraph 155	1
A	US 3 830 180 A (BOLTON H) 20 August 1974 (1974-08-20) column 7, line 28 -column 8, line 18; figures 11,12	1
	-/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

31 January 2003

Date of mailing of the international search report

07/02/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3016

Authorized officer

Lapeyrere, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IT 02/00526

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 22 08 139 A (GOEPPNER KAISERSLAUTERN EISEN) 30 August 1973 (1973-08-30) page 8, paragraph 1 ----	1
A	US 4 187 092 A (WOOLLEY RONALD L) 5 February 1980 (1980-02-05) column 1, line 65 -column 2, line 31 ----	1
A	FR 2 642 142 A (BUTAGAZ) 27 July 1990 (1990-07-27) page 6, line 18-21; figures ----	1
A	US 6 095 367 A (DAVIS KEVIN ET AL) 1 August 2000 (2000-08-01) column 9, line 6-27; figures -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IT 02/00526

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2757248	A	19-06-1998	FR 2757248 A1	19-06-1998
			AT 215202 T	15-04-2002
			CN 1240508 A ,B	05-01-2000
			DE 69711447 D1	02-05-2002
			DE 69711447 T2	14-11-2002
			EP 0960305 A1	01-12-1999
			ES 2175504 T3	16-11-2002
			WO 9826209 A1	18-06-1998
			JP 2001506737 T	22-05-2001
			KR 2000057555 A	25-09-2000
			US 6206027 B1	27-03-2001
US 2002046773	A1	25-04-2002	AU 8707101 A	22-03-2002
			WO 0220352 A1	14-03-2002
			US 2002046547 A1	25-04-2002
US 3830180	A	20-08-1974	NONE	
DE 2208139	A	30-08-1973	DE 2208139 A1	30-08-1973
US 4187092	A	05-02-1980	JP 54149393 A	22-11-1979
FR 2642142	A	27-07-1990	FR 2642142 A1	27-07-1990
US 6095367	A	01-08-2000	US 5577630 A	26-11-1996
			AT 219753 T	15-07-2002
			AU 690824 B2	30-04-1998
			AU 4855196 A	21-08-1996
			CA 2212016 A1	08-08-1996
			DE 69622022 D1	01-08-2002
			DE 69622022 T2	16-01-2003
			EP 0812293 A1	17-12-1997
			FI 973203 A	01-10-1997
			JP 10513420 T	22-12-1998
			NO 973558 A	23-09-1997
			NO 20013616 A	23-09-1997
			NZ 302486 A	26-08-1998
			WO 9623721 A1	08-08-1996

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)